



for each *BREATH*  
your patient takes

MILD



CAIRE solutions  
for LIFE.

A multitude of options for your patients,  
a simple decision for your business.

CAIRE's robust inventory of stationary concentrators boasts a wide variety of features and benefits. Depending on your business needs, there is a perfect choice for you and your patients.

- Treat a wide a range of patients—from pediatric to LTC
- Lightweight and power-efficient 2, 3, 5 and 10 LPM options
- Cost-effective, low-maintenance units
- Exclusive features like ultraSILENT and autoFLOW

Solutions for the entire continuum of CAIRE

Educate + Titrate = Saturate.

SEVERE

  
**CAIRE**<sup>®</sup>  
A Chart Industries Company

**Call 1.800.482.2473 to order!**  
[www.chartindustries.com/Respiratory-Healthcare](http://www.chartindustries.com/Respiratory-Healthcare)

# The Best Choices for Your Patients

CAIRE's solutions give providers the ability to help both the most clinically difficult patient and the most difficult to please—all with one product portfolio.

## CAIRE Companion 5™

### Compact Stationary Oxygen Concentrator

CAIRE's 5 LPM compact stationary is designed specifically for quality, performance and reliability. Using state-of-the-art technology and high-quality parts, the Companion 5 is a robust, durable, and technologically advanced option.

#### Patent-pending Technology

- autoFLOW™ technology optimizes overall performance
  - Adjusts valve cycle timing based on flow rates
  - Reduces compressor load by 25% at 2 LPM
  - Decreases wear on all major components
- ultraSILENT™ technology virtually eliminates purge (exhaust) noise

#### Ease of Service

- Limited connections and modular design for easy service
- No cabinet filter to clean; no 9-volt battery to replace
- Intake filter accessible without opening case

#### Eco Friendly

- Less than 300 W power consumption at 3.0 LPM and lower flow rates, reducing electrical costs



#### Ordering Information

Description	Part Number
Companion 5 Concentrator (120 V, 60 Hz), Non-OCSI, USA Cord	15067013
Companion 5 Concentrator (120 V, 60 Hz), OCSI, USA Cord	15067005



## NewLife® Elite

### Robust Stationary Oxygen Concentrator

The time-proven NewLife Elite concentrator delivers up to 5 LPM of therapeutic oxygen in home, hospital, and clinical settings. Units are available with an optional O<sub>2</sub> monitor.

- Flow meter available for pediatric and other low flow applications (0.125–2 LPM)
- Optional air outlet for nebulizer treatments

#### Ordering Information

Description	Catalog Number	Description	Catalog Number
120 V, 60 Hz Unit	AS005-1	120V, 60Hz (w/OM)	AS005-4

For dual flow, air outlet, or pediatric options please contact customer service for catalog numbers.

## NewLife® Intensity Series

### Power-Efficient Oxygen Concentrators up to 10 LPM

The NewLife Intensity series combines high pressure with high flow to create up to 10 LPM, operating at only 590 watts.

- Dual flow configuration optional
- Outlet pressure approximately three times higher than most other concentrators, designed to serve special applications:

- Trache set-up
- Large volume jet nebulizers
- Venti-masks
- Medication nebulizers
- Long oxygen tubing runs
- Connect two units together for higher flow rates

#### Ordering Information

Description	Catalog Number
120V/60Hz	AS099-100
120V/60Hz, OM	AS099-101
120V/60Hz, Dual Flow	AS099-1
120V/60Hz, Dual Flow, OM	AS099-4

Note: For NewLife Intensity 8 LPM Ordering Information, contact Customer Service.

# MILD



## VisionAire™ 2, 3 and 5 LPM

### VisionAire 2

#### For Pediatric Oxygen Needs

VisionAire 2 supports pediatric care with two types of precision flowmeters. The standard flowmeter has 1/8 LPM increments ranging from 1/8 LPM up to 2 LPM with CCM markings for easy conversion, and is suitable for adult use where lower power consumption and cooler operating temperatures are valued. The alternative flowmeter has 1/10 increments ranging from .10 LPM up to 1.0 LPM.

### VisionAire 3 & 5

#### Lightweight and Power Efficient at 3 & 5 LPM

VisionAire 3 and 5 are incredibly power-efficient stationary oxygen concentrators, using less than 300W at all flow rates. Offering up to 3 LPM and 5 LPM, respectively, the VisionAire 3 and 5 weigh only 30 lbs each.

### Cost-Effective, Maintenance-Free Units

The unique design of the VisionAire eliminates costly preventative maintenance schedules. This helps ensure that you maximize the potential of your equipment inventory while greatly reducing or eliminating any unnecessary down time.

Eliminating preventative maintenance costs, combined with low failure rates, creates a high-performing stationary concentrator with a low total cost of ownership.

### With Safety in Mind

Important safety features include a back-lined flow-meter for viewing accuracy and proper setting, and locking flow rates via easy regulator adjustment. Each concentrator is equipped with a resettable circuit breaker, a dual-function hour meter, and well-defined system alarms.

## Ordering Information

Description	Catalog Number**
VisionAire 2 w/oxygen monitor (115 V, 60 Hz unit), USA Cord	AS096-8
VisionAire 3 (115 V, 60 Hz unit), USA Cord	AS096-6
VisionAire 3 w/oxygen monitor (115V, 60 Hz unit), USA Cord	AS096-7
VisionAire 5 (115 V, 60 Hz unit), USA Cord	AS098-1
VisionAire 5 w/air outlet (115 V, 60 Hz unit), USA Cord	AS098-707
VisionAire 5 w/ oxygen monitor (115V/60Hz) USA Cord	AS098-4
VisionAire 5 w/oxygen monitor and air outlet (115 V, 60 Hz unit)	AS098-710

\*\* Other model units available, please contact Customer Service.

## Companion 5 Product Specifications

	Companion 5
Oxygen Concentration*	90% +5.5 / -3%
Flow Rate	Continuous 0.5 to 5.0 LPM
Oxygen Outlet Pressure	4.6 psig (31.7 kPa) nominal
Dimensions	21.5 in H x 12.5 in W x 13.5 in D 54.6 cm H x 31.8 cm W x 34.2 cm D
Weight	36 lbs. (16.3 kg)
Nominal Sound Level	40 dB(A) @ 2.0 LPM
Power Consumption	285 watts at 2.0 LPM, 350 watts maximum
Alarms	Power Failure, Flow Rate Error, General System Malfunction Low concentration (with optional OCSI)
Operating Environment	41° F to 104° F (5°C to 40°C), up to 10-95% relative humidity
Operating Altitude	-1,253 to 9,878 ft (-382 to 3,010 m)
Storage Environment	-40° F to 158° F (-40°C to 70°C), up to 95% relative humidity
Filters	Intake Filter (two year replacement), HEPA Filter (lifetime)



## NewLife Product Specifications

	NewLife Elite	NewLife Intensity
Oxygen Concentration*	1-3 LPM: 95% +0.5/-3% 4LPM: 92% +3.5/-3% 5LPM: 90% +3.5/-3%	8 LPM: 2-7 LPM: 92%+3.5/-3%; 8 LPM: 90%+5.5/-3% 10 LPM: 2-9 LPM: 92%+3.5/-3%; 10 LPM: 90%+5.5/-3%
Oxygen Outlet Pressure	7-9 psig (48-62 kPa)	20 psig (138 kPa)
Dimensions	28.5 in H x 15.7 in W x 14.5 in. D 72.4 cm H x 40.0 cm W x 36.8 cm D	27.5 in H x 16.5 in W x 14.5 in D (69.9 cm H x 41.9 cm W x 36.8 cm D)
Weight	54 lb (24.5 kg)	8 LPM: 54 lb (24.5 kg) 10 LPM: 58 lb (26.3 kg)
Nominal Sound Level	48 dB(A)	8 LPM: 52 dB(A); 10LPM: 55 dB(A)
Power Consumption	350 watts	8 LPM: 410 watts; 10 LPM: 590 watts
Alarms	Battery test, High Temperature, Power failure, High and low pressure, Low concentration (with optional oxygen monitor)	Battery test, High Temperature, Power failure, High and low pressure, Low concentration (with optional oxygen monitor)
Operating Environment	41° F to 104° F (5°C to 40°C), UP to 95% humidity	
Storage Environment	-4° F to 140° F (-20°C to 60°C), up to 95% relative humidity	
Filters	Gross Particle (Cabinet Filter), HEPA Filter (Lifetime), Optional Felt Filter	

## VisionAire Product Specifications

	VisionAire 2	VisionAire 3	VisionAire 5
Oxygen* Concentration	Up to 1 LPM at 95.0% +0.5%/-3%; 2 LPM at 90% +5.5%/-3%	0.5-3 liters per minute at 90% + 5.5/ -3%	1-5 liters per minute at 90% + 5.5/ -3%
Dimensions	20.8 in H x 14.1 W in x 11.5 in D (52.8 cm H x 35.8 cm W x 29.2 cm) D	20.8 in H x 14.1 in W x 11.5 in D (52.8 cm H x 35.8 cm W x 29.2 cm D)	20.8 in H x 14.1 in W x 11.5 in D (52.8 cm H x 35.8 cm W x 29.2 cm D)
Weight	30 lb; shipping weight - 37 lb (13.6 kg; shipping weight - 16.7 kg)	30 lb; shipping weight - 37 lb (13.6 kg; shipping weight - 16.7 kg)	30 lb; shipping weight - 37 lb (13.6 kg; shipping weight - 16.7 kg)
Power Consumption	200 watts	115 V, 60 Hz, 190 watts 230 V, 50 Hz, 175 watts	290 watts
Sound Level	45 dBA	45 dBA	45 dBA
Alarms	Power failure, High and low pressure, No flow, Low O <sub>2</sub> concentration (with optional oxygen monitor)	Power failure, High and low pressure, No flow, Low O <sub>2</sub> concentration (with optional oxygen monitor)	Power failure, High and low pressure No flow, Low O <sub>2</sub> concentration (with optional oxygen monitor)
Operating Environment	41 to 105°F (4 to 40°C), 15-95% humidity		
Storage Environment	-4 to 140°F (-20 to 60°C), 15-95% humidity		

\*Based on an atmospheric pressure of 14.7 psia (101 kPa) at 70° F (21°C). Operating unit outside of operational temperature range can affect performance  
**WARRANTY:** 3-Year Standard Warranty. Other warranty options available.

CAIRE, Inc.  
 2200 Airport Industrial Drive, Suite 500  
 Ball Ground, GA 30107  
 Toll-Free 1-800-482-2473