

# LNG TRANSPORT TRAILERS

PRESSURE TRANSFER UNIT

---



## LNG Delivery System

Chart's LNG line of transports are vacuum-insulated, cryogenic semi-trailers designed specifically for transporting liquefied natural gas over the road. These units exceed the requirements of an MC-338 highway trailer.

The trailers consist of a horizontal vacuum-insulated tank composed of an 'inner' pressure vessel and a structural frame/vacuum vessel 'outer' jacket. The outer jacket is made from lightweight, thin-gauge carbon and stainless steel, and the inner vessel is a 70 psig, ASME pressure vessel made from SA240 T-304 stainless steel. The ST-16300 trailer is built specifically to take on Canadian highways.

The control piping and instruments are located in the rear cabinet. Maximum use is made of the available space within the cabinet for easy access and operation. We use drop-down piping allowing for waist-high connection of the fill connectors (fill/drain and vapor return). The large capacity pressure-building coils and coil piping ensure off-loading by pressure transfer at rates up to 300 GPM.



# LNG TRANSPORT TRAILERS

PRESSURE TRANSFER UNIT



Fill/Drain and Vapor Return



LNG Pressure Transfer Trailer making delivery

## SPECIFICATIONS

Model	ST-12700	ST-16300
Gross Capacity	12,700 gal / 48075 ltrs	16,300 gal / 61,702 ltrs
LNG Capacity (at 70 psig / 4.826 barg)	38,476 lbs / 17,452 kg	50,400 lbs / 22,861 kg
Maximum Allowable Working Pressure	70 psig / 4.83 barg	70 psig / 4.83 barg
Length (overall)	48 ft / 14.6 m	53 ft / 16.2 m
Width (overall)	8 ft 6 in / 2.6 m	8 ft 6 in / 2.6 m
Height	12 ft 5 in / 3.74 m	12 ft 10 in / 3.91 m
Tare Weight	26,000 lbs / 11,793 kg	33,000 lbs / 14,966 kg
Design Codes	ASME Section VIII Division 1	ASME Section VIII Division 1
Axle Configuration	Tandem	Tri

## Scope of Supply

We are registered with the DOT and employ Design Certifying Engineers and Registered Inspectors. DOT requirements for transporting LNG by highway are found in Title 49 of the Code of Federal Regulations (49CFR): part 172.101, Table of Hazardous Materials and Special Provisions; part 173.318, Cryogenic Liquids in Cargo Tanks; and part 178.338, Insulated Cargo Tank (MC-338). The inner vessel is designed to meet or exceed the requirements for an ASME Code, Section VIII, Division 1 pressure vessel; the internal and external piping is in accordance with the requirements of ASME/ANSI B31.3 Piping Code; and Federal Motor Vehicle Safety Standards (FMVSS) are adhered to for all trailer automotive functions – running gear, lights, brakes, etc.

## Quality Commitment

We build our equipment to the highest standards and include a 5 year vacuum warranty. Our 5 North American service facilities and experienced members of our technical service group support every product Chart designs and manufactures.

**Contact us now for latest delivery on new units, or to inquire about refurbished trailers in stock.**

Chart Inc.  
U.S. : 1-800-838-0856  
Worldwide: 1-952-243-8800



©2021 Chart Inc.  
PN 14722928  
www.ChartLNG.com