

Balancing Valves and Assembly

Balancing Valves (BV) increase the efficiency and reliability of all divider block systems operating at high pressures by balancing the effect of injection point differentials on the divider block.

Recommended for divider block systems experiencing outlet pressure differentials $\geq 1,000$ psi (70 bar). The valves can be supplied factory preset to one of the charted set pressures or provided as components when field setting is required. However, balancing valves require a specific procedure to change the pressure settings in the field.


When ordered as an assembly (BVA), the balancing valve is manifolded together with a tube stem mounted on a male connector tube fitting. Operators can easily adjust the orientation of the pressure gauge in the field.



Balancing Valve Assembly

FEATURES


- Equalize divider block system outlet pressures to:
 - Maintain piston synchronization, prevent piston slap and reduce piston by-passing
 - Reduce premature wear of divider blocks
 - Reduce blown rupture disc problems
- Pressure gauge enables operator to easily balance outlet pressures
- Tube fittings allow for ease of installation along tubing lines
- Individual spring kits come with a lock wire and seal to prevent further tampering, and a punch tag for pressure set point identification



BALANCING VALVE PART NUMBERS

1. Select BV body type by indicating an 'S' for 1/4" tube x 1/4" tube or 'M' for 1/4" male NPT x 1/4" tube. This letter goes in the space labeled 'BV body type' below.

2. From the chart at the right, select the 4 digit set pressure that fits your application. This number fills in the four spaces indicated as 'set pressure'.



Use the following part numbers to order BV body types separately. Does NOT include spring kit.

PART NO.	DESCRIPTION
S - 650140000SS4R3A	BV body type 1/4" tube x 1/4" tube
M - 65014000SS4R3A1	BV body type 1/4" male NPT x 1/4" tube



BALANCING VALVE ASSEMBLY PART NUMBERS

1. Select BVA subassembly gauge style by indicating an 'S' for standard or 'E' for European CE. This letter goes in the space labeled 'gauge type' below.

2. From the chart at the right, select the 4 digit set pressure that fits your application. This number fills in the four spaces indicated as 'set pressure'.



Use the following part numbers to order BVA subassembly separately. Does NOT include spring kit.

PART NO.	DESCRIPTION
S - 65005000BVASSUB	BVA Subassembly with 6,000 psi (410 bar) standard gauge
E - 65005000BVAESUB	BVA Subassembly with 6,000 psi (410 bar) CE gauge



TECHNICAL SPECIFICATIONS

Set pressure range from 1,000 psi (69 bar) to 5,800 psi (400 bar)

BV Inlet: 1/4" OD tube or 1/4" Male NPT; Outlet: 1/4" OD tube

BVA Inlet: 1/4" OD tube; Outlet: 1/4" OD tube

BVA: 6,000 psi (410 bar) pressure gauge, standard or CE

BV & BVA SET PRESSURES, SPRING KIT PART NUMBERS:

SET PRESSURE PSIG (bar)	SPRING & TAG KIT PIN
1,000 (69), 1,100 (76) 1,200 (83), 1,300 (90) 1,400 (97)	650140SPRKITPPL Purple
1,500 (103), 1,600 (110) 1,700 (117), 1,800 (124) 1,900 (131), 2,000 (138) 2,100 (145), 2,200 (152)	650140SPRKITORN Orange
2,300 (159), 2,400 (165) 2,500 (172), 2,600 (179) 2,700 (186), 2,800 (193) 2,900 (200)	650140SPRKITBRN Brown
3,000 (207), 3,100 (214) 3,200 (221), 3,300 (228) 3,400 (234), 3,500 (241) 3,600 (248), 3,700 (255) 3,800 (262), 3,900 (269)	650140SPRKITWHT White
4,000 (276), 4,100 (283) 4,200 (290), 4,300 (296) 4,400 (303), 4,500 (310) 4,600 (317), 4,700 (324) 4,800 (331), 4,900 (338)	650140SPRKITRED Red
5,000 (345), 5,100 (352) 5,200 (359), 5,300 (365) 5,400 (372), 5,500 (379) 5,600 (386), 5,700 (393) 5,800 (400)	650140SPRKITGRN Green



CPI, part of the Howden group, provides industry leading lubrication system products and services, partnering with our customers to develop individual solutions to their unique lubrication needs. From individual components to complete, turnkey systems, we can provide the resources and expertise to ensure your compressor operates at peak performance and longevity.